





## Ready 8 MT 1~ 2p

### Technical specification



Installation: S - Portable Semi permanent, Wet



Skatīt uzstādīšanas instrukciju

Height

10 20000



Note: Picture might not correspond to the current configuration.

#### General

Light compact submersible pump in aluminum that can handle abrasive media at the construction site, mine, or at home.

#### Impeller

Impeller material	Thermoplastic polyurethane
Discharge Flange Diameter	50 mm
Inlet diameter	15 mm
Impeller diameter	8 mm
Number of blades	6 mm

#### Motor

Motor #	B2008 212 12-08-28B-W 0.75KW
Approval	Standard
Stator variant	2
Frequency	50 Hz
Rated voltage	230 V
Number of poles	2
Phases	1
Rated power	0.75 kW
Rated current	4.2 A
Starting current	19 A
Rated speed	2825 rpm
Power factor	
1/1 Load	1.00
3/4 Load	1.00
1/2 Load	1.00
Efficiency	
1/1 Load	78.5 %
3/4 Load	79.0 %
1/2 Load	75.1 %

#### Configuration

Project

Project ID

Created by

Created on

15.06.2016

Last update

SIA LAKALME

Reģ. Nr. LV40003379590

Adrese

Baldones iela 12  
Rīga, LV-1007  
LATVIJA

Tālrunis

(+371) 67892745

Fakss

(+371) 67606360

E-pasts

[lakalme@lakalme.lv](mailto:lakalme@lakalme.lv)